





FEATURES

Chassis: Arrow XT, PAP

Engine: Cummins X15 600 HP

Transmission: Allison 5th Gen 4500 EVS P,

6-speed, push button

 Front Axle: TAK-4, Non-drive, 24,000 lbs.

- Rear Axle: Meritor RT58-185, 58,000 lbs.
- Front Wheels: Alcoa Aluminum
 22.5" x 13"
- Rear Wheels: Alcoa Aluminum and Steel, Hub Pilot, Tandem 22.5" x 9"
- Bumper: 19" extended
- 300 US gallon Poly water tank
- Waterous CSU 1,500 GPM pump
- Foam system provisions
- Seating Capacity: 6 seats

Stock No. 32876

Arrow XT™ 100' PAP

Designed and built with an emphasis on heavy-duty, the Arrow XT meets the demands of any high volume department with its rugged and dependable chassis and an all-business cab interior.

Big power, at 94.75" wide the Arrow XT cab is the narrowest in the industry, providing up to 600 hp engines for maximum performance in a narrow, maneuverable fire truck. "Extreme Tilt" cab that allows easy inspection & maintenance of the drive train.

Massive 13.38" 120 ksi steel frame rails for superior handling & reduced frame deflection.











Providing expert truck equipment solutions across Canada comemerg.ca 1-800-665-6126

View File Created 27-JUL-2020 13:53:38 DIRENGIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO HINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION,
HINOR DETAILS NOT SHOWN. CHASSIS
Arrow XT Chassis
ENCINE
600 HP X15 Engine (2) WHELEN M9 L.E.I STABILIZER WARNING LIGHTS EACH SIDE 0 \$ 3 5 1 3 5 CAB
6710 Notched Arrow XT Cab
BUNPER
19° Extended Stainless Steel AIR INLET WITH DISCONNECT—
FITTING MOUNTED IN A RECESSED
ALUMINUM TREADPLATE BOX L. HORNER, ME CORPUCE, IN IN DESAME, SPEN AUFS-EET, LOUIS ON ROTHER SIZE OF THE CORP.

2. MINISTE CHARGE CHARGE AND AUFS-EET, LOUIS CHARGE AND AUFS-EET, LOU 0 9 AXLE, FRONT, CUSTON
22,800 Lb TAK-4 AxLe m AXLE, REAR 58,000 Ub Meritor Axle 0 ⊚⊡ () L.E.D. LIGHT EACH SIDE 再列列 0 TRANSMISSION Allison 5th Gen, 4500 EVS P 6.5 7.7 6.5 Ħ CENTER SEASON PARE, IN COMPANIENT POR 900 0028

AUMENT POR VIDEN SEASON PARE VIDEN S 0 o ::: PUNPHOUSE
52° Control Zone Side Mount
PUNP
2000 GPM Materious CSU - ACROIN CORD REEL MODEL ERAC-15-10 WITH 200" OF 10/4 CORD, CAPTIVE ROLLER ASSEMBLY AND ALUMINUM TREADPLATE ENCLOSURE **,**, 0 0 . RUNING BOARD EACH SIDE **©** 0 CROSSLAYS, 1.50"
(2) 1.50" Standard Capacity
CROSSLAYS, 2.50"
(1) 2.50" Standard Capacity 1000" OF 5.00" DJ POLY HOSE -(1) WHELEN MICRO PIONEER - STERAUP STEP WITH GRIP PATTERN \prod DESIGNATED WALKWAY SPEEDLAYS
SpeedLays Not Required
GENERATOR
Horrison 6kM MCR Hydraulic 0 SAPETY
Side Roll and
Frontal Impact Protection Ø 6 AND PATHWAY KWAKINGS - WHELEN PIONEER PCPSN2 L.E.D. LIGHT WITH ALUNINUM TREADPLATE ENCLOSURE EACH SIDE HARNING LIGHT EACH SIDE CO WELEN PIONEER PEPI --₩ Z7JUL20 JGA NDA PIERCE

Z5SEP18 NNA TH5 NOCEL

REV DATE BY CH ARRON XT 0 PIERCE FIELD UNIT

PIERCE FOR APPLETON, WISCONISN

PORE DUG

APPROV XT NO. 3 2 8 (2) WHELEN ME L.E.D.
STOP/TAIL LIGHTS
DIRECTIONAL LIGHTS
BACK-UP LIGHTS
MOUNTED IN WHELEN
ME PIERCE BEZELS (1) WHELEN TAL65 L.E.D. -TRAFFIC DIRECTING LIGHT IN 4-WAY BOX A CONNON BEZEL EACH SIDE RETRAC HEATED/REMOTE CONTROL MIRRORS MITH CONVEX SECTION WARNING LIGHTS
EACH SIDE PROVISIONS FOR — SWITCH FOR DECK LIGHT CO WHELEN LIGHTS -(2) MÆLEN MICRO PIONEER MPBN L.E.D. DECK LIGHTS -8.00" COUNTERNE (OHTED NOTCHED REAR BUMPER NITH ANGLED CORNERS CWERNS EACH SIDE PIERCE BACK UP CAMERA TITLE 100" Steel Platfor Alum Body
COMPT, DRIVER SIDE PRONT
FMFD Sealup who Obute
COMPT, DRIVER SIDE PRONT
FMFD Bottup out lift-up Removed
COMPT, PASSENGER SIDE FRONT
FML Height Bottup Foremand
COMPT, PASSENGER SIDE RAK
Full Height Bottup out liftup Removed HARNING LIGHTS ON FRONT OF BASKET -(1) WHELEN PIONEER PFP2
L.E.D. TIP LIGHT CENTERE 100 AERIAL PLATFORM & BODY ASSEMBLY Pierce STABILIZER CONTROLS —— 5.00" AERIAL INLET-(2) GROVER AIR HORNS 00000 MANUFACTURING INC. 2 (2) WHELEN FREEDOM IV — 21.50° L.E.D. LIGHTBURS MOUNTED AT 30° ANGLE Foam System
Husky 3 Single Agent Foom System
Foam Cell
20 Gollon Foom Cell, Non-Reduced Noter \triangleright 300 Gallon Ó (PAP100A) F (1) WELEN SA31SP SPEAKER
NITH S/STL GRILLE
GRIER HOSE TRAY
FOR 125' OF 1.75' HOSE
NITH 1.50' OUTLET AND SHIVEL HATER TANK
PAP Notched Poly Nater Tank WITCH FOR HOSEBED LIGHT # 00000 · — EQUIPMENT STORED
AT THE REAR
ONE 26', 2-SEC 1200A
ONE 14', 2-SEC 701
ONE 15', 2-SEC 701 JOB NO.
SOLE
1;24
DRAW BY
MWA
CHECKED BY
THS WITH SMOOTH DOOR 32876 25JUN18 29JUN18 DATE

ı

 \neg