





FEATURES

Chassis: Enforcer

Engine: Cummins L9 450 HP

Transmission: Allison 5th Gen3000 EVS P,

5-speed, push button

• Front Axle: Oshkosh TAK-4, Non-drive,

19,500 lbs.

Rear Axle: Meritor RS26-185,

27,000 lbs.

Wheels: Aluminum

Bumper: 19" extended

1000 US gallon Poly water tank

Darley 2,000 GPM pump with

Magna transmission

Magna transmission

Foam System: Husky 3

Seating Capacity: 6 seats

Enforcer™ Pumper

Proven reliability returns. The Pierce Enforcer chassis is more capable than ever. With TAK-4® independent front suspension and the Cummins L9 450 HP engine the Enforcer performs like never before.

Maximum 50-degree cramp angle & 15-degree angle of approach for improved maneuverability in those tight areas & challenging situations. The steps are lower to the ground & offset to function like a stair step, making it easier for firefighters to enter & exit the cab.









Stock No. 35315

Providing expert truck equipment solutions across Canada comemerg.ca 1-800-665-6126

View File Orested 22-WY-2020 11:19:13 DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION. Side Roll and Frontal Impact Protection FIRE SUPPRESSION COMPT, PUMPER, RIGHT SIDE 161" ROLLUP FULL Height Front & Roor FDLER COMPT, PUMPER, LEFT SIDE WATER TANK
1000 Gallon Poly Noter Tank
COMPT, PUMPER, REAR
44.50' FF Rollup Rear Compt $Foam \ \ Cell 1$ 20 Gallon Foam Cell, Not Reduced Water CHASSIS
AXLE, FRONT, CUSTOM
19,500 UB TAK-4 AXLO CROSSLAYS, 1.50"
(2) 1.50" Standard Capacity
CROSSLAYS, 2.50"
(1) 2.50" Standard Capacity Foam System Husky 3 Single Agent Foom System 52° Control Zone Side Mount BODY Long Aluminum 2nd Gen Pumper TRANSMISSION ALLison 5th Gen, 3000 EVS F GENERATOR
Generator Not Required SPEEDLAYS
SpeedLays Not Required ENCINE
450 HP Cunnins L9 Engine AXLE, REAR 27,000 Lb Meritor AxLe CAB 7010 Enforcer Cab BUMPER CHASSIS Enforcer Chassis PUMPER 2000 GPM Danley PUMPHOUSE B 0 D Y PUMP . OR 1.50 OUTS 111 2 AND PINS AND SITES, LOCKIED IN CORRES BARNY
2. MORE LINE RECORDING THE MORSHAM, SERVE INTERPLECT LIAZZION DIRECTOR SITES OF THE CAR
2. MINISTON COMMON LIAZZION DIRECTOR SITES SITES SITES SITES
2. MINISTON COMMON LIAZZION DIRECTOR SITES SITES SITES
3. SITE AUSTRALE SERVES IN COMMON DIRECTOR SITES SITES
3. SITE AUSTRALE SITES SITES SITES SITES SITES SITES SITES
3. SITES AUSTRALE SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES SITES
3. SITES SITES SITES SITES SITES
3. SITES
3. SITES SITES
3. SITES SITES
3. SITES SITES
3. SITES SITES
3. SITE 0 L.E.D. SOBNE LIGHT EACH SIDE 0 201.00 MB -385.00 (32"-1.00") APPROX OAL * 0 0 * L.E.D. SCENE LIGHT EACH SIDE o, ***** 9.0 REV DATE BY CH ENFORCER CUSTOMER APPROVAL (1) WELEN MS L.E.D.

WARNING LIGHT
(1) WELEN OST L.E.D.

DIRECTIONAL LIGHT IN
A COMMON BEZEL EACH SIDE CO WELEN ME L.E.D.

KARNING LIGHTS
STOP/TAIL LIGHTS
DIRECTIONAL LIGHTS
BACK-UP LIGHTS
HACK-UP LIGHTS
NS PIERCE BEZELS (1) CUP SWITCH FOR REAR SCENE LIGHTS VIEW CAMERA

(1) CUP SWITCH FORHOSE BED LIGHTING (1) 2.50° QUILET -RETRAC HEATED/RENOTE CONTROL MIRRORS WITH CONVEX SECTION CO WELEN LIGHTS

L.E.D. WARNING LIGHTS WARNING LIGHTS
EACH SIDE CO WHELEN PIONEER-TRAFFIC DIRECTING LIGHT WELEN FREEDOM IV — PIERCE FOR Pierce Field Unit CHASSIS TITLE Pierce Pumper Approval Drawing Pience (2) GROVER AIR HORNS þ # **00000** HOSEBED CAPACITY

BD 1

SOO OF SOOT D.J. POLY HOSE

1 ED 2

1 HOOD OF S.OF D.J. POLY HOSE

1 ED 3

200' OF S.OF D.J. POLY HOSE HOSE BED DIVIDERS 3531 ... ⊗...

71.78

Θ

-12.50

DIO-SHETY LADDER STORAGE

(1) 24' 2-SECTION 900A

(1) 14' ROPE POLE

(1) 6' F/G PIKE POLE

(1) 6' F/G PIKE POLE

(2) ALMINIM PIKE POLE TUBES

0000

-CENTER HOSE TRAY FOR 125' OF 1.75' HOSE WITH ALUMINUM TREADPLATE COVER

— (1) WHELEN SA315P SPEAKER WITH S/STL GRILLE

(1) FEDERAL 028 SIREN

MANUFACTURING INC.

JOB NO. 35315

SOUR DATE

1, 24 DATE

DAWN BY 20MAY20

ORECOS BY 21MAY20

SHET SIZE SHET NO.

1 OF 1

21MAY20 20MAY20

SAD

 \Box

L.E.D. VISOR LIGHT