



BODY 110' Single Axle Platform Aluminum Body COMPT, LEFT SIDE FRONT Full Height RollUp Forward COMPT, LEFT SIDE REAR Full Height RollUp Rearward COMPT, RIGHT SIDE FRONT Full Height RollUp Forward COMPT, RIGHT SIDE REAR Full Height RollUp Rearward	WATER TANK 500 Gallon Poly Water Tank Foam System Plumbing For Future Foam System Foam Cell 20 Gallon Foam Cell, Non-Reducing Water
--	---

CHASSIS Enforcer Chassis ENGINE 450 HP Cummins L9 Engine	CAB 7010 Notched Enforcer Cab BUMPER 19" Extended Stainless Steel	AXLE, FRONT, CUSTOM 24,000 Lb TAK-4 Axle AXLE, REAR 33,500 Lb Meritor Axle	TRANSMISSION Allison 5th Gen, 3000 EV5 P	PUMPHOUSE 52" Control Zone Side Mount PUMP 2000 GPM Waterous CSU	CROSSLAYS, 1.50" (2) 1.50" Standard Capacity CROSSLAYS, 2.50" (1) 2.50" Standard Capacity	SPEEDLAYS Speedlays Not Required GENERATOR Generator Not Required
---	--	---	--	---	--	--

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONE 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- BATTERY CHARGER LOCATED BEHIND DRIVERS SEAT
- BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE CAB
- L.E.D. LIGHT STRIPS LOCATED IN THE HOSE BED PER SHOP ORDER
- SIX ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER
- FOUR FLOOR MOUNTED SLIDE-OUT TRAYS IN COMPARTMENTS PER SHOP ORDER
- NON-RAISED AERIAL PEDESTAL
10. 1250 GPM HIGH FLOW WATERWAY
- NO LIMITED RETRACTION
- MOUNTING PROVISIONS FOR FRONT INLET

CUSTOMER APPROVAL APPROVED BY: _____ DATE: _____			JOB NO.	36448
			SCALE	DATE
CHASSIS DATA	TITLE	110' ASCENDANT AERIAL LADDER AND BODY ASSEMBLY	DRAWN BY	TKA
MAKE	FOR	PIERCE FIELD UNIT APPLETON, WI	CHECKED BY	THS
PIERCE	DWG NO.	36448AD	SHEET SIZE	SHEET NO.
MODEL	REV		D	1 OF 1