

ASCENDANT 107' SINGLE AXLE HEAVY-DUTY AERIAL LADDER



GO WHERE NO AERIAL APPARATUS HAS GONE BEFORE. WITHOUT COMPROMISE.

The Ascendant® 107' heavy-duty steel ladder has truly redefined the single rear axle aerial market, providing firefighters with an unprecedented 107' of vertical height and 100' of horizontal reach without compromising on water capacity, performance, or safety. The heavy-duty 100,000 psi high strength steel ladder was purpose built using proven engineering. The Ascendant is rated at a 750 lb dry and a 500 lb wet tip load capacity with an additional 100 lb equipment allowance. It can flow up to 1,500 gpm and is capable of a store front blitz feature as standard.

The Ascendant is designed to be operated at a 12 percent uphill slope and a 9 percent downhill slope. As standard, the frame rails, torque box, and pedestal are e-coated for improved corrosion resistance. The design, strength, and durability of the Ascendant ladder have been rigorously tested and third-party certified to stringent UL Type I requirements.

The 107' Ascendant heavy-duty ladder is available on a wide range of body styles, providing firefighters flexibility and a wide range of options to meet each department's needs. Choose from a quint body style, a Texas Chute Out style body for departments desiring a side stacked hosebed, and a true truck company body style with no pump or tank. Compartment space varies, ranging from 144 cubic feet to 306 cubic feet depending upon the body style selected. In total, with water and foam, the 107' Ascendant on a 33,500 lb single rear axle can accommodate an impressive 500 gallons with 2,500 lb of equipment, full hose complement, and a big block engine (if desired).



Specifications

Custom Chassis	Arrow XT™, Enforcer™, Impel®, Velocity®
Vertical Height	107'
Horizontal Reach	100'
Operating Range	-10° to 77°
Payload Capacity	750 lb dry/500 lb wet
Wind & Ice Ratings	Up to 50 mph winds & .25" of ice
Flow Capacity	1,500 gpm
Stabilizers	1 set of H-style & 1 down-jack
Stabilizer Spread	18'
Rear Axle	Single
Tank Capacities	Up to 500 gallons
Pump Range	Waterous, Hale, Darley Midship, PTO
PUC™ Availability	Yes
Hosebed Capacities	1,000' of 5" or split load 700' of 5" & 600' of 3" hose
Ladder Complement	Minimum of 115'
Ladder Warranty	20-yr structural
Patents	Issued & pending

www.piercemfg.com



Pierce Manufacturing Inc., An Oshkosh Corporation Company
P.O. Box 2017, Appleton WI 54912-2017 USA

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment. All measurements are nominal values.

© Pierce Manufacturing Inc., Pierce, the Pierce logo, Ascendant, Impel, and Velocity are registered trademarks and Arrow XT, Enforcer, and PUC are trademarks of Pierce Manufacturing Inc., Appleton, WI. Printed in U.S.A.

All other trademarks are the property of their respective owners.

P-0115-ASDNT107HDSGLSS 11/18