

75' ALUMINUM AERIAL LADDER



HIGH PERFORMANCE ON A SINGLE REAR AXLE WITH A SHORT WHEELBASE.

The Pierce® 75' aluminum aerial ladder is designed with high-strength aluminum extrusions resulting in an extremely durable ladder. Get an impressive 750 lb dry tip load rating capable of flowing up to 1,500 gpm. You can add up to 100 lb of additional firefighting equipment at the tip without reducing the rated load capacity. Besides its impressive tip load rating, the 75' aluminum aerial ladder has a 2.5:1 structural safety factor, a 35 mph wind load rating, and can operate with up to .25" of ice buildup.

The ladder features a removable egress, making it easy to repair if it is ever damaged without having to replace the entire fly section. The single set of H-style stabilizers allows for quicker and easier setup. Using a third-party, every Pierce aerial is certified to the stringent UL Type I requirements.



Specifications

| | |
|--------------------|---|
| Custom Chassis | Arrow XT™, Dash® CF, Enforcer™, Impel®, Quantum®, Velocity® |
| Vertical Height | 75' |
| Horizontal Reach | 67'9" |
| Operating Range | -8° to 76° |
| Payload Capacity | 750 lb dry/500 lb wet |
| Wind & Ice Ratings | Up to 35 mph winds & .25" of ice |
| Flow Capacity | 1,500 gpm |
| Stabilizers | 1 set of H-style |
| Stabilizer Spread | 16' |
| Rear Axle | Single |
| Tank Capacities | Up to 500 gallons |
| Pump Range | Waterous, Hale, Darley Midship, PTO |
| PUC™ Availability | Yes |
| Hosebed Capacity | 1,000' of 5" hose |
| Ladder Complement | Minimum of 115' |
| Ladder Warranty | 20-yr structural |

www.piercemfg.com



Pierce Manufacturing Inc., An Oshkosh Corporation Company
P.O. Box 2017, Appleton WI 54912-2017 USA

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment. All measurements are nominal values.

© Pierce Manufacturing Inc., Pierce, the Pierce logo, Dash CF, Impel, Quantum, and Velocity are registered trademarks and Arrow XT, Enforcer, and PUC are trademarks of Pierce Manufacturing Inc., Appleton, WI. Printed in U.S.A.
All other trademarks are the property of their respective owners.